ELIKO TECHNOLOGY

FLEXILINE

BLDC SERIES

FLXBL60-300-ELC-O

Compact design - simple integration - high power density



Integrated BLDC Servo Motor
with CANopen Interface

CANopen

Key Benefits

Compactness

60 mm square flange, 108 mm length and embedded electronics reduce cabinet space, wiring effort and integration volume.

Power density

353 W rated power and 1.95 Nm peak torque in a compact FlexiLine package.

Ease of use

CANopen communication, USB configuration, configurable I/O and integrated protections simplify commissioning.

Technical Data

Item Name	UM	FLXBL60-300-ELC-N-O
Rated Voltage	V	48
Rated Power	W	353
Rated Speed	RPM	5200
Rated Current	A	9,2
Peak Current	A	27,6
Rated Torque	Nm	0,65
Peak Torque	Nm	1,95
Torque constant	Nm/A	0,07
Voltage constant	V/krpm	4,2
Resistance line-line	Ω	0,29
Inductance line-line	mH	0,35
Number of poles	-	10
Rotor moment of inertia	$kg.cm^2$	0,39
Flange	mm	60
Overall length	mm	108
Motor weight	g	900


Integrated Controller & Interface

Item Name	UM	FLXBL60-300-ELC-N-O
Main supply range	VDC	12-75
Nominal supply	VDC	48
Communication	-	CANopen, USB configuration
CANopen network	-	Up to 127 stations
Digital inputs	-	3 opto-isolated, configurable
High-speed capture	µs	5 minimum pulse width in latch/capture mode
Digital outputs	-	2 opto-isolated outputs
Output supply / current	-	12-30 VDC, up to 30 mA
Analog input	-	1 differential, ±10 V
Analog resolution	bit	12
STO input	VDC	12-28.8, nominal 24
Protection functions	-	Short-circuit, over-current, over/under-voltage
Operating temperature	°C	-10 to +40
Humidity	%	<85, non-condensing

Data tolerances: ±10%. Subject to change without prior notice.

Drawing

FLXBL60-300-ELC-N-O



Dimensions in mm

Curves

