









剖面 A-A


比例2:1















PIN	Function
1	Control 48V supply return
2	Control 48V supply return
3	Protective Earth
4	Control 48V supply
5	Control 48V supply

局部视图 D


比例2:1



PIN	Function
1	EtherCAT_IN_TX_P
2	EtherCAT_IN_TX_N
3	EtherCAT_IN_RX_P
4	EtherCAT_IN_RX_N


局部视图 A

比例2:1



局部视图 B

比例2:1




PIN	Function
1	EtherCAT_OUT_TX_P
2	EtherCAT_OUT_TX_N
3	EtherCAT_OUT_RX_P
4	EtherCAT_OUT_RX_N

局部视图 C

比例2:1

No.OF POLES	10
DC LINK VOLTAGE	48 VDC
RATED POWER	628 W
RATED TORQUE	1.5N.m
RATED SPEED	4000±10% RPM
RATED CURRENT	17 A
RESISTANCE LINE-LINE	0.087 Ω
INDUCTANCE LINE-LINE	0.41 mH
VOLTAGE CONSTANT	6.5±10% V/KRPM
TORQUE CONSTANT	0.088Nm/A
ROTOR MOMENT OF INERTIA	0.7Kg.cm2
INSULATION CLASS	F
MAX.RADIAL FORCE	335N
MAX.AXIAL FORCE	150N
WEIGHT	2KG
PROTECTION LEVEL	IP65, SHAFT SEALING IP54SHAFT



局部视图 E

比例2:1

PIN	Function
1	Control 24V supply return
2	Opto-isolated digital input 1
3	Opto-isolated digital input 2
4	Opto-isolated digital input 3
5	Digital input return
6	Opto-isolated digital output 1
7	Opto-isolated digital output 2
8	Digital output return
9	Analog input 1
10	Analog input 1 complement
11	Control 24V supply
12	STO 1 opto-isolated input
13	STO 2 opto-isolated input
14	STO signal return
15	Not Connected

Revision	Indice	Date	Modification	Cartographer	Verifier
A	1	2026/3/20	Initial version	Wu XinBo	ER

annotation :

ELIKO Technology
Room 101-102,
Building 12
No. 285, Wuyi Road
Changzhou Economic
Development Zone
Jiangsu Province,
China

This document is the property of Eliko Technology. Without the prior authorization of our company, it shall not be disclosed to or copied by any third party.

materials:	estimated weight:	General tolerance:	surface roughness:
surface treatment:	gram	ISO 2768-mk	√Rax.x
surface smoothness:			

DIN ISO 13715

Title:	
N° Document :	MOTELI00445
N° Article :	FLXBL80-600-ELE-N

scale: 1:2	paper size: A3	pagination: 1/1	software: Solidworks	version: 2020